

|   |   |
|---|---|
| <b>Product introduction:</b>                  | Reflective Sheet is material used for public signs, or advertisements. And it's has various grade like commercial grade, engineering grade, high intensity grade, and etc. is digital printable for solvent and eco-solvent inks.                             |
| <b>Composition</b>                            | PVC Film glass beads, Release paper & PSA glue  |
| <b>Film Thickness:</b>                        | 180micron   |
| <b>Weight of film:</b>                        | 309g/sqm  |
| <b>Weight of release paper:</b>               | 150g/sqm  |
| <b>Sizes:</b>                                 | 1.22m x 45.7m /roll   |
| <b>Color:</b>                                 | White/Yellow  |
| <b>Type of Adhesive Glue:</b>                 | PSA   |
| <b>Coefficient of retro-reflection (CPL):</b> | 30  |
| <b>Retro-reflection condition:</b>            | Observation Angle: 0.2°, Entrance Angle: - 4°   |
| <b>Storage Condition:</b>                     | The reflective sheeting should be made store in an aeration, dry, shadow place. It should be laid on a pallet and can't be on the floor directly. Each pallet can only be loaded not more than 5 layers of cartons. The storage temperature should be 18-30℃. |
| <b>Printing:</b>                              | Applicable for solvent and eco-solvent digital printing   |
| <b>Durability:</b>                            | 1-2years  |
| <b>Application:</b>                           | 1) Road traffic signs;<br>2) Work zone signage;<br>3) Advertising signage;<br>4) Vehicle number plates;<br>5) Various vehicle markings.   |

**Compatible With**  
UV, Solvent, ECO Solvent, Latex  
*Printers*



Digital Printing Materials By  
**PEOPLE**  
OUTDOOR

