

P.O.XBanner 440g

Laminated Banner

Digital Printing Materials By

PEOPLE
OUTDOOR

Item	Unit	Value	Test Method
Base Fabric	Denier	500DX500D	(High tenacity yarn) 100%PES
Construction	Weaving/inch	9x9	/
Weight of fabric	Gsm/m2	47±5	DIN53352 BS3424 Method5B
Weight of PVC	Gsm/m2	393±5	DIN53352 BS3424 Method5B
Total weight	Gsm/m2	440±10	DIN53352 BS3424 Method5A
Thickness	mm	0.35±0.02	DIN EN ISO 2286-3
Width	cm	Up to 510	/
Tensile Strength	N/5cm	Warp	800
		Weft	700
Tearing Strength	N	Warp	85
		Weft	75
Adhesion	N/5CM	60	DIN53357 BS3425 Method9B
Temperature Resistance	°C	-20~70	DIN53357 BS3425 Method10
Lacquering	None		
Flammability	We can achieve: B1, B2, NFPA701, etc.		
LOW CADMIUM & HEAVY METALS	We can be applied for : Cadmium free (EN71-3) or Reach Compliance		

Compatible With

UV, Solvent, ECO Solvent, Latex

Printers



Digital Printing Materials By



Declaration by PEOPLE OUT DOOR: Please choose PEOPLE products suitably according to relative provisions or industrial standards. PEOPLE bears the responsibility for specified technical and performance data on this page only. PEOPLE is not responsible for any other liability. (The technical data on this page is calculated on average, and ±5% tolerance is acceptable)