

P.O.COATED 510g

Coated Backlit

Digital Printing Materials By
PEOPLE
 OUTDOOR

Item	Unit	Value		Test Method
Base Fabric	Denier	1000DX1000D		(High tenacity yarn) 100%PES
Construction	Weaving/inch	20x20		/
Weight of fabric	Gsm/m2	175 +/- 10		DIN53352 BS3424 Method5B
Weight of PVC	Gsm/m2	335 +/- 10		DIN53352 BS3424 Method5B
Total weight	Gsm/m2	510 +/- 20		DIN53352 BS3424 Method5A
Thickness	mm	0.40 +/- 0.02		DIN EN ISO 2286-3
Width	cm	Up to 510		/
Tensile Strength	N/5cm	Warp	2100	DIN53352 BS3424
		Weft	1850	
Tearing Strength	N	Warp	250	DIN53356 BS3424
		Weft	230	
Adhesion	N/5CM	80		DIN53357 BS3425 Method9B
Temperature Resistance	°C	-20~70		DIN53357 BS3425 Method10
Lacquering	None			
Flammability	Can be apply for: B1, B2, M2, NFPA701, etc.			
LOW CADMIUM & HEAVY METALS	We can be applied for : Cadmium free (EN71-3) or Reach Compliance			

Compatible With
 UV, Solvent, ECO Solvent, Latex
Printers



Declaration by PEOPLE OUT DOOR: Please choose PEOPLE products suitably according to relative provisions or industrial standards. PEOPLE bears the responsibility for specified technical and performance data on this page only. PEOPLE is not responsible for any other liability. (the technical data on this page is calculated on average, and ±5% tolerance is acceptable)