

# P.O.EBanner 510g

Laminated Banner

Digital Printing Materials By

**PEOPLE**  
OUTDOOR

Item	Unit	Value	Test Method
<b>Base Fabric</b>	Denier	1000DX1000D	(High tenacity yarn) 100%PES
<b>Construction</b>	Weaving/inch	9x9	/
<b>Weight of fabric</b>	Gsm/m2	87±5	DIN53352 BS3424 Method5B
<b>Weight of PVC</b>	Gsm/m2	423±5	DIN53352 BS3424 Method5B
<b>Total weight</b>	Gsm/m2	510±10	DIN53352 BS3424 Method5A
<b>Thickness</b>	mm	0.38±0.02	DIN EN ISO 2286-3
<b>Width</b>	cm	Up to 510	/
<b>Tensile Strength</b>	N/5cm	Warp	1350
		Weft	1150
<b>Tearing Strength</b>	N	Warp	160
		Weft	135
<b>Adhesion</b>	N/5CM	60	DIN53357 BS3425 Method9B
<b>Temperature Resistance</b>	°C	-20~70	DIN53357 BS3425 Method10
<b>Lacquering</b>	None		
<b>Flammability</b>	We can achieve: B1, B2, NFPA701, etc.		
<b>LOW CADMIUM &amp; HEAVY METALS</b>	We can be applied for : Cadmium free (EN71-3) or Reach Compliance		

**Compatible With**  
UV, Solvent, ECO Solvent, Latex  
*Printers*



Declaration by PEOPLE OUT DOOR: Please choose PEOPLE products suitably according to relative provisions or industrial standards. PEOPLE bears the responsibility for specified technical and performance data on this page only. PEOPLE is not responsible for any other liability. (The technical data on this page is calculated on average, and ±5% tolerance is acceptable)