

# P.O.C Blockout

Coated Blockout 800 gsm

Digital Printing Materials By  
**PEOPLE**  
 OUTDOOR

Item	Unit	Value		Test Method
<b>Base Fabric</b>	Denier	1000DX1000D		(High tenacity yarn) 100%PES
<b>Construction</b>	Weaving/inch	20X20		/
<b>Weight of fabric</b>	Gsm/m2	175±10		DIN53352 BS3424 Method5B
<b>Weight of PVC</b>	Gsm/m2	625±10		DIN53352 BS3424 Method5B
<b>Total weight</b>	Gsm/m2	800±20		DIN53352 BS3424 Method5A
<b>Thickness</b>	mm	0.55±0.02		DIN EN ISO 2286-3
<b>Width</b>	cm	Up to 500		/
<b>Tensile Strength</b>	N/5cm	Warp	2250	DIN53352 BS3424
		Weft	2600	
<b>Tearing Strength</b>	N	Warp	370	DIN53356 BS3424
		Weft	320	
<b>Adhesion</b>	N/5CM	100		DIN53357 BS3425 Method9B
<b>Temperature Resistance</b>	°C	-20~70		DIN53357 BS3425 Method10
<b>Lacquering</b>	No			
<b>Flammability</b>	Can be apply for B1, B2, M2, NFPA701 etc.			
<b>LOW CADMIUM &amp; HEAVY METALS</b>	We can be applied for : Cadmium free (EN71-3) or Reach Compliance			

**Compatible With**  
 UV, Solvent, ECO Solvent, Latex  
 Printers



Declaration by PEOPLE OUT DOOR: Please choose PEOPLE products suitably according to relative provisions or industrial standards. PEOPLE bears the responsibility for specified technical and performance data on this page only. PEOPLE is not responsible for any other liability. (The technical data on this page is calculated on average, and ±5% tolerance is acceptable)