

Description

Film: 100 micron Glossy white, monomeric calendered PVC film

Adhesive: Permanent clear solvent based acrylic adhesive

Release liner: One side PE and silicon coated kraft paper, 140gsm

Width: 0.914/1.06/1.27/1.37/1.52m

Length: 50/100m

Shelf Life: Up to 1 year at 20°C and relative humidity of 50%

Durability: Up to 1 year

Item	Unit	Value	Test Method
Thickness - film	µm	100	GB/T6672-2001
Thickness - finished product	µm	260	GB/T6672-2001
Adhesive weight	g/m ²	20-22	FINAT12
Elongation at break MD	%	≥100	GB/T1040.1-2006
Elongation at break CD	%	≥70	GB/T1040.1-2006
Tensile Strength at break MD	N/25 mm	35-45	GB/T1040.1-2006
Tensile Strength at Break CD	N/25 mm	30-40	GB/T1040.1-2006
Dimensional stability MD	%	≤1.0	FINAT14
Dimensional stability CD	%	≤0.7	FINAT14
Initial Adhesion	N/25mm		Finat9
180 Peel - 20 minutes	N/25 mm	13-16	Finat1
180 Peel - 24 hours	N/25 mm	16-20	Finat1
Applied Printers	Inkjet printing with Solvent/ ECO Solvent based inks, UV or Latex inks		

Compatible With
UV, Solvent, ECO Solvent, Latex
Printers



Digital Printing Materials By
PEOPLE
OUTDOOR

