

P.O.Mesh 270g

Coted Mesh With Liner

Digital Printing Materials By

PEOPLE
OUTDOOR

Item	Unit	Value		Test Method
Base Fabric	Denier	1000DX1000D		(High tenacity yarn) 100%PES
Construction	Weaving/inch	9X13		/
Weight of MESH	Gsm/m2	260 +/- 20		DIN53352 BS3424 Method5B
Weight of pvc liner	Gsm/m2	100		DIN53352 BS3424 Method5B
Total weight	Gsm/m2	360 +/- 20		DIN53352 BS3424 Method5A
Width	cm	Up to 320		/
Tensile Strength	N/5cm	Warp	1000	DIN53352 BS3424
		Weft	1100	
Tearing Strength	N	Warp	220	DIN53356 BS3424
		Weft	260	
Temperature Resistance	°C	-20~70		DIN53357 BS3425 Method10
Lacquering	None			
Flammability	\			
LOW CADMIUM & HEAVYMETALS	\			

Compatible With
UV, Solvent, ECO Solvent, Latex
Printers



Declaration by PEOPLE OUT DOOR: Please choose PEOPLE products suitably according to relative provisions or industrial standards. PEOPLE bears the responsibility for specified technical and performance data on this page only. PEOPLE is not responsible for any other liability. (The technical data on this page is calculated on average, and $\pm 5\%$ tolerance is acceptable)